

200⁺ 切削條件表 **P385**
Cutting Condition

Square Type - Long Flute - Multiple Flutes

多刃長刃強力立銑刀

200 PLUS


HRC 65

A D
B C
A#B#C#D

L3 L4
L1#L2#L3#L4

● Super Ultra Fine Micro Grain Carbide

● WC=91 Co=9 HRA=93.2 Rupture=4000N/mm² Grain Size=0.2μm



Dimension 規格					Purchase Code 採購代碼		
Diameter	Flute Length	Full Length	Shank Diameter	Flutes	MODE	Coating 塗層	
d 刃徑	l 刃長	L 全長	D 柄徑	Z 刃數	型號	TISIN+	P-nACO
6	25	75	6	5	P-SFULVT0605	.06	.07
8	35	100	8	7	P-SFULVT0807	.06	.07
10	45	100	10	7	P-SFULVT1007	.06	.07
12	50	100	12	7	P-SFULVT1207	.06	.07
16	65	150	16	9	P-SFULVT1609	.06	.07
20	75	150	20	9	P-SFULVT2009	.06	.07
25	80	150	25	9	P-SFULVT2509	.06	.07

- HRC > 40
 - HRC > 45
 - HRC > 50
 - HRC > 55
 - HRC > 60
 - HRC > 65**
-

Application 適用材質：

★ Perfect 最推薦 ◎ Excellent 適合 ○ Good 佳

Coating 塗層	Carbon steel, Alloy steel 炭素鋼, 合金鋼	Pre-harden steel 預硬鋼	High-hardened 高硬度鋼					Stainless steel 不鏽鋼	Titanium alloy 鈦合金	Nickel/Inconel alloy 鎳基合金	Copper alloy 銅合金, 銅	Aluminum alloy 鋁合金
		~45HRC	~50HRC	~55HRC	~60HRC	~65HRC						
TISIN+	○	○	○	◎	◎	◎						
P-nACO	○	○	○	◎	◎	★						

Unit/單位: mm